

DPS-F1D08

8 CH CCTV Power Supply



KEY FEATURES

- Highly Efficient & Consumes Low Power.
- Stabilized Output, Low Interference, Surge Protected.
- Provision of 8 channel connection with LED indicator.
- In-built power cord with 3 Pin Plug.
- Highly Integrated SMPS Switcher IC Design.
- Insulated Cabinet Protection.
- Short Circuit Auto Restart.
- Input Voltage Range -100VAC-265VAC 50/60Hz.
- Output Voltage - 12V \pm 5%.
- Enhanced ventilation for cooling and improve the longevity.



SPECIFICATION

POWER SUPPLY

Channel	8CH
Model	DPS-F1D08
Input Voltage Range	100VAC(Min)~265VAC (Max)
Frequency	50Hz - 60Hz
Output Voltage	12V \pm 5%
Output Current	1A per channel (Max)
Line Regulation	\leq 5%
Setup Rise Time	\leq 5S
Hold-up Time	30mS
Inrush Current	< 50A
Leakage Current	<0.25mA
Auto Reset	Yes, During overload & short circuit
Overload Protection Auto restart	Yes
Ripple	\leq 200mV
Surge Protection	3KV
Efficiency	\geq 68%
Input Nominal Voltage	150VAC-240VAC
Housing	ABS White
Store Temperature	-20° to +80° C
Working Humidity	10 ~ 90%
Working Temperature	0°C to +50°C
Dimension	153 mm X 98.4 mm X 38.8 mm