

D-Link 2U DVR Enclosure with Bottom Openable Feature

D-Link Presents 2U Wall-mount DVR Enclosures designed exclusively for CCTV DVR Storage & Safety with Specially designed bottom openable feature for ease of Access & Service of the DVR.

In case of an event, DVR is the Most Important Component in your CCTV Setup as it stores the invaluable Data, Safeguard your DVR with D-Link 2U Wall-Mount Enclosure.

It is provided with a special bottom openable feature with Lock & Key for ease of Service as the BNC Connectors in the DVR are connected at the rear of the DVR making it difficult to access DVR in a Wall-mount DVR, therefore it has always been a challenge servicing the DVR for any add, move changes forcing the installers to either leave extra cable inside the Wall-mount Enclosure so that the DVR can be pulled out for Service or else DVR is kept SIDE ON so that it can be serviced from 1 side through the front door.

DVR Enclosures are fabricated out of CRCA steel, CNC programmed, punched, bended, welded and powder coated with highest quality standards with lock & key for the safety.

Configuration for standard Enclosures are:

Welded frame integrated with side walls and vented top cover with fan mounting provision, rear side of the Enclosure having wall mounting provision, front glass door with lock & Key and Bottom openable feature for ease of access & Service of the DVR.

Features:

- Conforms to DIN 41494 OR equivalent ISO Standards
- Adjustable 19" equipment mounting verticals provide better mounting flexibility and maximizes the usable mounting space
- Depth adjustable mounting slots
- Precision engineering capabilities and best efficient software configuration product technology provide the best product quality and fastest delivery in the industry
- Top and bottom Panel with ventilation and cable entry facility
- Provision to mount cooling fans on the top panel
- Powder coated finish with pretreatment process meeting all industry standards
- Grounding and Bonding Options. 100% assured compatibility with all equipment conforming to DIN 41494 (General industrial standard for equipment)



Technical Data:

Rack Standard	:	Conforms to DIN 41494 or equivalent standard
Construction	:	Welded
Front Door	:	Lockable Toughened Glass Door
Basic Frame	:	Steel
Equipment Mounting	:	DIN Standard Slots
Mounting Angle	:	19" Mounting angles made of formed steel
Standard Finish	:	Powder Coated
Top and Bottom Cover	:	Welded to Frame, Bottom openable for DVR Service
Standard Color	:	Grey
Static Load	:	15 kgs

Part Code & Dimensions:

Part Code	Height OD	Height Usable	Height Usable	Width	Usable	Depth	Usable
	In mm(H)	in mm (H)	in U (H)	In mm(W)	Width(W)	In mm(D)	In mm(D)
NWR-2U-5540-GR-DVR	169	89	02U	550	19"	400	270

D-Link Part No	Item Description
D-Link Unloaded Wall-mount Enclosure	
NWR-2U-5540-GR-DVR	Wall Mount 2U x 550 W x 400 D – Bottom Openable with Lock & Key Front Glass Door (Tinted, Toughened) with Lock & Key, 2 pairs of 19" Mounting Rails with U-Marking Welded Side Walls With Metal Engraved D-Link Logo