

DVR-F2104-M1H5

4CH H.265+ 2MP Lite DVR




KEY FEATURES

- Supports 4CH & 1 SATA slot
- Supports AHD/TVI/CVI/IP cameras up to 2MP
- Supports H.264/H.264+/H.265/H.265+
- Supports Smart Playback & Analytics
- Supports 2 extra IP Channel
- Supports 3G/4G Wi-Fi
- Supports Cloud storage
- Supports Video Quality Detection (VQD)

DVR-F2104-M1H5

4CH, 2MP Lite DVR

INTERFACE



SPECIFICATION

VIDEO & AUDIO INPUT

| | |
|----------------|--|
| Video Input | 4ch BNC interface (1.0Vp-p, 75 Ω) |
| TVI / CVI /AHD | 1080P, 720P |
| IPC | Up to 6ch 2MP |
| Audio Input | 1-ch, RCA (2.0 Vp-p, 1 KΩ) |
| Two way Talk | 1-ch, multiplex with Audio Input (RCA) |

VIDEO & AUDIO OUTPUT

| | |
|--------------|---|
| HDMI | 1ch resolution: 1920×1080/60Hz, 1280×1024/60Hz, 1280×720/60Hz, 1024×768/60Hz |
| VGA | 1ch resolution: 1920×1080/60Hz, 1280×1024/60Hz, 1280×720/ 60Hz, 1024×768/60Hz |
| CVBS output | NA |
| Audio Output | 1-ch, RCA (Linear, 1kΩ) |

RECORDING

| | |
|-------------------|--|
| Compression | H.264/H.264+/H.265/H.265+ |
| Resolution | 4ch 1080P Lite@15fps; 960H1/D1/CIF real time |
| Frame Rate(fps) | 1fps-15fps |
| Video Bit Rate | 11Kbps-2707Kbps |
| Record Mode | Manual, Schedule, Alarm |
| Audio Compression | G.711a |
| Audio Bit Rate | 64Kbps |

PLAYBACK & BACKUP

| | |
|---------------|---|
| Playback Mode | Smart Playback/Normal/Time Division/ Label/ Event, Picture Playback |
| Playback Rate | 4ch Playback |
| Backup Mode | USB Device/Network |

SMART FUNCTION

| | |
|----------------------------|---|
| Smart Detection for Analog | 1Ch line crossing detection, area Intrusion |
| Smart Playback for Analog | line crossing detection, area Intrusion |
| Cloud Storage | Support |
| Cloud Upgrade | Support |

NETWORK

| | |
|------------------|---|
| Ethernet | 1 RJ-45 10/100 Mbps self-adaptive Ethernet interface |
| Network Function | HTTPs, HTTP, TCP/IP, IPv4, UPnP, Onvif2.6, RTSP, RTCP, UDP, SMTP, IGMP, NTP, DHCP, DDNS, FTP, P2P |
| Smart Phone | IOS (iPhone, iPad), Android (Phone, Pad) |

| HARD DISK | |
|--------------------------------------|--|
| SATA | 1 HDD |
| Capacity | Up to 10TB capacity for each HDD |
| EXTERNAL INTERFACE | |
| Serial Interface | NA |
| USB Interface | 2 × USB 2.0 |
| GENERAL | |
| Power Supply | DC12V, 2A |
| Power Consumption | ≤15W(without HDD) |
| Working Environment | -10°C~+55°C / 10%~90%RH |
| Dimension (W×D×H) | 250 x 230 x 45mm |
| Weight (without HDD) | 1.5kg |
| Certification | CE, BIS |
| SYSTEM MANAGEMENT | |
| Mobile Software | D-Link Smart CCTV App |
| Desktop Software | DSVS (D-Link Smart Video Surveillance) |
| System Requirement for Web Interface | IE |