


DVR-F2116-L1H5

16CH, 1080P Lite DVR



KEY FEATURES

- 16CH, 1SATA
- Support AHD/TVI/CVI/IP Technologies
- Support AHD/TVI/CVI/IP cameras up to 2MP
- Support H.265+/H.265 or H.264+/H.264
- Supports Tamper & Video Loss Detection
- Support 3G/4G Wi-Fi
- Support Cloud storage

DVR-F2116-L1H5

16CH, 1080P Lite DVR

INTERFACE



SPECIFICATION

VIDEO & AUDIO INPUT

Video Input	16ch BNC interface (1.0Vp-p, 75 Ω)
TVI / CVI /AHD	1080P, 720P
IPC	Up to 16ch Resolution up to 2MP
Audio Input	1-ch, RCA (2.0 Vp-p, 1 KΩ)
Two way Talk	1-ch, multiplex with Audio Input (RCA)

VIDEO & AUDIO OUTPUT

HDMI	1ch, resolution: 1920×1080/60Hz,1280×1024/60Hz, 1280×720/ 60Hz
VGA	1ch, resolution: 1920×1080/60Hz,1280×1024/60Hz, 1280×720/6 0Hz
Audio Output	1-ch, RCA (Linear, 1kΩ)

RECORDING

Compression	H.264/H.264+/H.265/H.265+
Resolution	16ch 1080P Lite@12fps; 960H/D1/CIF real time
Frame Rate(fps)	1fps-12fps
Video Bit Rate	11Kbps-2291Kbps
Record Mode	Manual, Schedule, Alarm
Audio Compression	G.711a
Audio Bit Rate	64Kbps

PLAYBACK & BACKUP

Playback Mode	Normal/Time Division/ Label/ Event/ Picture Playback
Playback Rate	16ch Playback
Backup Mode	USB Device/Network

CLOUD FUNCTION

Cloud Storage	Support
Cloud Upgrade	Support

NETWORK

Ethernet	1 RJ-45 10 /100 Mbps self-adaptive Ethernet interface
Network Function	HTTPs,HTTP,TCP/IP,IPv4,UPnP,Onvif2.6,RTS P,RTCP,UDP,SMTP,IGMP,NTP,DHCP,DNS,DD NS, FTP, P2P
Smart Phone	IOS(iPhone, iPad), Android(Phone, Pad)

HARD DISK	
SATA	1 HDD
Capacity	Up to 8TB capacity for each HDD
EXTERNAL INTERFACE	
Serial Interface	NA
USB Interface	2 × USB 2.0
GENERAL	
Power Supply	DC12V, 2A
Power Consumption	≤15W(without HDD)
Working Environment	-10°C~+55°C / 10%~90%RH
Dimension (W×D×H)	250 x 230 x 45mm
Weight (without HDD)	1.5kg
Certification	CE, BIS
SYSTEM MANAGEMENT	
Mobile Software	D-Link Smart Plus CCTV App
Desktop Software	D-Link Smart Video Surveillance 2.0
System Requirement for Web Interface	IE