

# **DVR-F2116-M1H5**


# **16CH H.265+ 2MP Lite DVR**



## **KEY FEATURES**

- Supports 16CH, 1SATA
- Supports AHD/TVI/CVI/IP cameras up to 2MP
- Supports H.264/H.264+/H.265/H.265+
- Supports Smart Playback & Analytics
- Supports 3G/4G Wi-Fi
- Supports Cloud storage
- Supports Video Quality Detection (VQD)

#### **INTERFACE**



### SPECIFICATION

| VIDEO & AUDIO INPUT        |   |  |
|----------------------------|---|--|
| Video Input                | 16ch BNC interface (1.0Vp-p, 75 $\Omega$ )  |  |
| TVI / CVI /AHD             | 1080P, 720P   |  |
| IPC                        | Up to 16ch 2MP  |  |
| Audio Input                | 1-ch, RCA (2.0 Vp-p, 1 KΩ)  |  |
| Two way Talk               | 1-ch, multiplex with Audio Input (RCA) )  |  |
| VIDEO & AUDIO OUTPUT       |   |  |
| HDMI                       | 1ch, resolution:<br>1920×1080/60Hz,1280×1024/60Hz,1280×720/60<br>Hz,1024×768/60Hz                               |  |
| VGA                        | 1ch, resolution:<br>1920×1080/60Hz,1280×1024/60Hz,1280×720/<br>60Hz,1024×768/60Hz                               |  |
| CVBS output                | NA  |  |
| Audio Output               | 1-ch, RCA (Linear, 1kΩ)   |  |
| RECORDING                  |   |  |
| Compression                | H.264/H.264+/H.265/H.265+   |  |
| RESOLUTION                 | 16ch 1080P Lite@12fps; 960H1/D1/CIF real time   |  |
| Frame Rate(fps)            | 1fps-12fps  |  |
| Video Bit Rate             | 11Kbps-2291Kbps   |  |
| Record Mode                | Manual, Schedule, Alarm   |  |
| Audio Compression          | G.711a  |  |
| Audio Bit Rate             | 64Kbps  |  |
| PLAYBACK & BACKUP          |   |  |
| Playback Mode              | Smart Playback/Normal/Time Division/ Label/<br>Event/ Picture Playback  |  |
| Playback Rate              | 16ch Playback   |  |
| Backup Mode                | USB Device/Network  |  |
| SMART FUNCTION             |   |  |
| Smart Detection for Analog | 2CH line crossing detection, area Intrusion   |  |
| Smart Playback for Analog  | Line crossing detection, Area Intrusion,<br>Motion detection  |  |
| Cloud Storage              | Support   |  |
| Cloud Upgrade              | Support   |  |
| NETWORK                    |   |  |
| Ethernet                   | 1 RJ-45 10/100 Mbps self-adaptive Ethernet interface  |  |
| Network Function           | HTTPs,HTTP,TCP/IP,IPv4,UPnP,Onvif2.6,RTS<br>P,RTCP,UDP,SMTP,SNMP,Multicast,IGMP,N<br>TP,DHCP,DNS,DDNS, FTP, P2P |  |
| Smart Phone                | IOS (iPhone, iPad), Android (Phone, Pad)  |  |

## **DVR-F2116-M1H5**

## 16CH, H.265+ 2MP Lite DVR

| HARD DISK                            |  |
|--------------------------------------|--|
| SATA                                 | 1 HDD                                  |
| Capacity                             | Up to 10TB HDD support                 |
| EXTERNAL INTERFACE                   |  |
| Serial Interface                     | NA                                     |
| USB Interface                        | 2 × USB 2.0                            |
| GENERAL                              |  |
| Power Supply                         | DC12V, 2A                              |
| Power Consumption                    | ≤15W(without HDD)                      |
| Working Environment                  | -10°C~+55°C / 10%~90%RH                |
| Dimension (W×D×H)                    | 250 x 230 x 45mm                       |
| Weight (without HDD)                 | 1.5kg                                  |
| Certification                        | CE, BIS                                |
| SYSTEM MANAGEMENT                    |  |
| Mobile Software                      | D-Link Smart CCTV App                  |
| Desktop Software                     | DSVS (D-Link Smart Video Surveillance) |
| System Requirement for Web Interface | IE                                     |

