

DNR-F5108-L5

8CH Network Video Recorder



KEY FEATURES

- 8CH, 1 SATA NVR
- Support up to 5MP IPC
- Support H.265+/H.265/H.264+/H.264
- Support Smart Playback & Analytics
- Support 3G/4G Wi-Fi Connectivity
- Support Motion based Cloud Storage
- Support Onvif 2.6

INTERFACE



SPECIFICATION

Video & Audio Input

IP Video Input	8ch
Audio Input	N/A

Video & Audio Output

HDMI	1ch, resolution:1920×1080/60Hz,1440×900/60Hz,1280×1024/60Hz, 1280×720/60Hz,1024×768/60Hz
VGA	1ch, resolution: 1920×1080/60Hz,1440×900/60Hz, 1280×1024/60Hz, 1280×720/60Hz, 1024×768/60Hz
Audio Output	N/A

Recording

Compression	H.265+/H.265 /H.264+/H.264
Resolution	5MP /4MP / 3MP /1080P /720P /D1/CIF /QCIF

Playback & Backup

Playback Mode	Smart/ Normal/ Time Division/ Label/ Event/ Picture/ Log Playback
Decoding Capability	4CH@1080P(25fps)
Backup Mode	USB Device/Network

Advanced Features

Smart Detection	Area Intrusion, Line crossing, Region Entrance /Region Exiting, Fast Moving, Object Missing, Unattended Object, Face Detection, Human Detection, Vehicle Detection
Smart Playback	Line Crossing/Area Intrusion /Motion Detection
Cloud Storage	Support
Cloud Upgrade	Support

Network

Incoming Bandwidth	40Mbps
Outgoing Bandwidth	20Mbps
Ethernet	1 RJ-45 10 /100 Mbps self-adaptive Ethernet interface
Network Compatibility	HTTP, HTTPS, TCP/IP, IPv4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, IP Filter, DDNS, FTP, P2P, ONVIF 2.6
Smart Phone	IOS(iPhone, iPad), Android(Phone, Pad)

Hard Disk	
SATA	1 SATA interface
Capacity	Up to 8TB capacity for each HDD
External Interface	
USB Interface	Front panel: 1 × USB 2.0 Rear panel: 1 × USB 2.0
General	
Power Supply	DC12V/1.5A
Power Consumption	≤10W (without HDD)
Working Environment	-10°C~+55°C / 10%~90%RH
Dimension (W×D×H)	250x230x45mm
Weight	≤1.5Kg
Certification	CE, BIS
System Management	
Mobile Software	D-Link Smart Plus CCTV App
Desktop Software	DSVS2.0 (D-Link Smart Video Surveillance 2.0)
System Requirement for Web Interface	IE