

DPS-F1B05

CCTV Single Output 5A Power Supply



KEY FEATURES

- Metal Case Power Supply.
- Surge Protection provided.
- Stabilized Output with Low Interference.
- Overload & Short Circuit Protection
- Thermal protected auto restart
- LED Indicator to indicate Power ON
- Output Voltage 12V - 5A
- Input Voltage-180VAC-264VAC 50/60Hz



SPECIFICATION

POWER SUPPLY

D-Link SKU	DPS-F1B05
Product Description	CCTV Single Output 5A Power Supply
Input voltage	180~264VAC
Output voltage	12V DC
Current Range	0~5A
Rated Power	60W
Ripple & Noise (max;)	100-150-mV P-P
Voltage dj; Range	11.4~13.6V
Line Regulation	±1;0%
Voltage Tolerance	±2;0%
Setup Rise time	600ms, 30ms at full load
Hold Up Time (Typ;)	13ms at full load
Load Regulation	±5;0%
Temperature coefficient	±0;03%/°C (0~50°C)
Frequency Range	47~63HZ
Efficiency (Typ;)	84%
C Current (Typ;)	5mA@115VAc & 3mA/230VAC
Inrush Current (Typ;)	20A/115VAC 40A/230VAC
Leakage Current	<2mA / 240VAC
Overload	110~200% rated output power, Protection type: Shut down O/P, re -power on to recover
Isolation Resistance	I/P-O/P, I/P-FG, O/P-FG:100M Ohms / 500VDC / 25°C/ 70% RH
Working Humidity	20~90% RH Non-condensing
Vibration	10 ~ 500Hz, 3G 10min;/1 cycle,60min; each along X, Y, Z axis
Dimension	167(L) x 96(W) x 52mm(H)
Store temperature	-20~+85°C, 10~95%RH
Working temperature	-20~+40°C
Withstand Voltage	I/P-O/P: 1; 5KVAC I/P-FG: 1; 5KVAC O/P-FG:0; 5KVAC