

DPS-F1C04

4 CH CCTV Power Supply



KEY FEATURES

- Highly Efficient & Consumes Low Power
- Stabilized Output, Low Interference, Surge Protected
- LED Indicators for each channel
- In-built power cord with 3 Pin Plug
- Highly Integrated SMPS Switcher IC Design
- Insulated Cabinet Protection
- Short Circuit Auto Restart
- Input Voltage-100VAC-240VAC 50/60Hz
- Output Voltage - 12V- 1 AMP max per channel



SPECIFICATION

POWER SUPPLY

Input Voltage Range	100VAC-240VAC
Frequency	50Hz/60Hz
Output Voltage	12V±5%
Output Current	1A per Channel
Line Regulation	≤5%
Setup Rise time	≤5S
Hold up time	10ms
Inrush current	< 50A
Leakage Current	<0.25mA
Auto Reset During overload and short circuit without Interrupting the output voltage.	YES
Overload Protection Auto restart	YES
Ripple	≤80mV
surge protection	3.5KV
Efficiency	≥80%
Operating Voltage (100VAC - 300VAC)	YES
Housing	ABS white Plastic
Store Temperature	-20°C~ +80°C
Working Humidity	10%~90%
Working Temperature	0°C~ +50
Dimension	L: 153mm, W: 98mm, H: 33.83mm